

STAINLESS STEEL WIRE CLOTH

| MESH | WIRE DIAMETER | WIDTH OF OPENING | % OPEN AREA |
|--------------------------|----------------------|-------------------------|--------------------|
| 4 x 4 | 0.0350 | 0.2150 | 74.0% |
| 6 x 6 | 0.0320 | 0.1320 | 62.4% |
| 8 x 8 | 0.0280 | 0.0970 | 60.2% |
| 10 x 10 | 0.0250 | 0.0750 | 56.3% |
| 20 x 20 | 0.0140 | 0.0360 | 51.8% |
| 30 x 30 | 0.0110 | 0.0220 | 44.9% |
| 40 x 36 | 0.0090 | 0.0160 | 41.0% |
| 50 x 40 | 0.0080 | .012/.017 | 41.0% |
| 50 x 246 Twin Warp | .0045/.0045 | | |
| 50 x 250 Plain Dutch | .0055/.0045 | | |
| 60 x 50 | 0.0065 | .0102/.0135 | 41.4% |
| 80 x 70 | 0.0055 | 0.0073 | 22.8% |
| 100 x 90 | 0.0045 | .0055/.0066 | 32.6% |
| 120 x 108 | 0.0035 | 0.0050 | 36.0% |
| 150 x 140 | 0.0026 | | |
| 165 x 800 Twilled Dutch | .0028/.0018 | | |
| 200 x 190 | 0.0021 | | 33.6% |
| 200 x 1400 Twilled Dutch | .0028/.0016 | | |
| 325 x 325 | 0.0014 | | 30.0% |